



Release Liner Liner Side Adhesive Carrier Air Side Adhesive	Liner:	76lb polycoated bleached kraft, silicone treated on both sides
	LS Adhesive:	Non-sensitizing acrylic (M109)
	Backing/Carrier:	0.5 mil polyester film
	AS Adhesive:	Non-sensitizing acrylic (M109)

Applications

- Surgical drape fabrication and assembly
- Medical device attachment
- Medical device assembly

• Surgical drape attachment: drape to drape, drape to skin

Features	Benefits
Polyester Film Carrier	 Support for aid in processing and application
	 Easily conforms to various surface types
 Non-Sensitizing Acrylic Adhesive 	 High tack and good shear properties
	 Stable to EtO and gamma sterilization
76lb PC Bleached Kraft	 Low COF for hand apply applications
	 Good dimensional stability and moisture
	resistance

Typical Test Values

	Standard UOM	Metric UOM	Test Method			
Total Thickness w/liner	8.8 mils	0.224 mm	PSTC 133			
Adhesive Thickness (Air Side)	1.4 mils	0.036 mm	PSTC 133			
Carrier Thickness	0.5 mils	0.013 mm	PSTC 133			
Adhesive Thickness (Liner Side)	1.4 mils	0.036 mm	PSTC 133			
Liner Thickness	5.5 mils	0.140 mm	PSTC 133			
Adhesion to Steel (Air Side)	130 oz/in	14.22 N/cm	PSTC 101 Mod			
Adhesion to Steel (Liner Side)	145 oz/in	15.86 N/cm	PSTC 101 Mod			
Product Safety						

The base adhesives in this medical product have been tested in accordance with ISO 10993 and found to be noncytotoxic, non-sensitizing, and non-irritating.

In accordance with FDA cGMP requirements, Berry reminds the customer that ultimate fitness for use must be determined by the manufacturer of the finished device.

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryglobal.com 1/11/18



Authorized Distributor, Converter, and Fabricator www.jbc-tech.com